Fast 02 2C Pro Plus Anti-intrusion fogging security systems

PROFESSIONAL LINE

It is the ideal fogging system to protect medium areas like large shops, homes, and generally all professional applications where top security technology is needed. It is equipped with **two cylinders** for a very convenient, reliable and redundant shooting, shoots up to 400 m³ of dense fog in 25 seconds. It is very fast and competitive.

It is prearranged to an easy wall installation and it has a lower compartment to equip boards or accessories if needed.

UR Fog fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR Fog fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



A serial bus allows to add additional boards to each UR Fog system for an easier interface with all kinds of alarm centrals.



Plus electronic board

OPTIONAL ACCESSORIES



Battery 2Ah



UR Fog S.r.l.

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037 E-mail: info@urfog.com



Powerful and fast fogging system, can cover up to **1200** m³ in **25 seconds** (400 m³ recommended visibility).



Double cylinder patented technology

One of our patent and the best way to emit

fog, thanks to the automatic switch between the first and the second cylinder (when the first one is empty). They are disposable and easy to replace.



Vertical recharge Liquid quantity 600 ml Horizontal recharge Liquid quantity 600 ml



Exclusive patented system that allows to automatically detects if the nozzle has been obstructed by sending a signal in case of tampering.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot f or a long time in absence of mains power; temperature is constantly stable.

Long lasting operation time without mains The innovative thermal insulation of the heater allows UR Fog systems to work for a long period of time without mains power: from 1,5 h up to 3,5h!

Anti-intrusion fogging security systems

GENERAL SPECIFICATIONS

Weight of the fog machine Weight with packaging about Units on one pallet 100×120 Dimension of the machine Dimension of the packaging 25,0 X37,0 XH47,0 Colors White Working time without mains power Heat up time from cold Vertical mounting Horizontal mounting Serial usb port for monitoring you KG 24 24 25,0 X27,0 XH43,5 25,0 X37,0 XH47,0 about 2 hours about 2 hours yes
Units on one pallet 100×120 Dimension of the machine 21,5 X27,0 XH43,5 Dimension of the packaging Colors White Working time without mains power Heat up time from cold Vertical mounting Horizontal mounting yes
Dimension of the machine 21,5 X27,0 XH43,5 Dimension of the packaging 25,0 X37,0 XH47,0 Colors White Working time without mains power Heat up time from cold Vertical mounting Horizontal mounting yes
Dimension of the packaging 25,0 X37,0 XH47,0 Colors White Working time without mains power Heat up time from cold Vertical mounting Horizontal mounting yes
Colors white Working time without mains power about 2 hours Heat up time from cold about 90 minutes Vertical mounting yes Horizontal mounting yes
Working time without mains power about 2 hours Heat up time from cold about 90 minutes Vertical mounting yes Horizontal mounting yes
Heat up time from cold about 90 minutes Vertical mounting yes Horizontal mounting yes
Vertical mounting yes Horizontal mounting yes
Horizontal mounting yes
Serial ush port for monitoring
Serial distributioning yes
Nozzle tamper yes
Serial bus for standard protocol yes
Alarm kit opzional

FOGGING SYSTEM

New heating system plus	yes
Coverage in a single shot (1,5 m visibility)	up to 1200 m ³
Coverage in a single shot (recommended density)	up to 400 m³
Max seconds of fog emission	25 sec
Max fog emitted with full fog tank	1800 m³
Number of cylinders	2
Fog tank capacity	2 x 600 ml
Shooting specification	programmable in seconds
Cylinder model	vertical / horizontal
Cylinder included	2
Double fog tank advantage	yes

STANDARD

Coi	mplies with european CE	yes
Fo	g fluid is certified	yes
Ме	ets european standard	yes

ELECTRICAL SPECIFICATIONS

Power supply	230 V or 110 V
Average power consumption	42 W
Back up battery	yes
Optional demo/antirobbery kit	yes
Inputs wired arming and shooting	yes
Outputs wired	yes
Standard communication protocol	yes



UR Fog S.r.l

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037 E-mail: info@urfog.com