Fast 03 2C Pro Plus Anti-intrusion fogging security systems

PROFESSIONAL LINE

It is the ideal fogging system to protect small volume spaces, shops, homes and generally all professional applications where top security technology is needed.

It is equipped with **two cylinders** for a very convenient, reliable and redundant shooting, shoots up to 200 m³ of dense fog in 15 seconds. **It is very fast and competitive**.

It is prearranged to an easy wall installation and it has a lower compartment to equip boards or accessories if needed.

UR Fog fogging systems are innovative in their technology and performances, in order to guarantee the most effective protection against thefts and they have different patents.

UR Fog fogging systems are certified after European regulation. Fog fluid is assessed as not dangerous for people and animals and does not leave residuals.



A serial bus allows to add additional boards to each UR Fog system for an easier interface with all kinds of alarm centrals.



Plus electronic board

OPTIONAL ACCESSORIES



Battery 2Ah



UR Fog S.r.l.

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037 E-mail: info@urfog.com



Powerful and fast fogging system, can cover up to **600 m³ in 15 seconds** (200 m³ recommended visibility).



Double cylinder patented technology

One of our patent and the best way to emit fog, thanks to the automatic switch between the first and the second cylinder (when the first one is empty).

They are disposable and easy to replace.



Vertical recharge Liquid quantity 600 ml Horizontal recharge

Liquid quantity 600 ml



Exclusive patented system that allows to automatically detects if the nozzle has been obstructed by sending a signal in case of tampering.



Thanks to the massive insulation UR FOG fogging systems have a very low power consumption and can shoot f or a long time in absence of mains power; temperature is constantly stable.

Long lasting operation time without mains The innovative thermal insulation of the heater allows UR Fog systems to work for a long period of time without mains power: from 1,5 h up to 3,5h!

Fast 03 2C Pro Plus Anti-intrusion fogging security systems

GENERAL SPECIFICATIONS

Weight of the fog machine	about 14 KG
Weight with packaging about	15 KG
Units on one pallet 100×120	24
Dimension of the machine	21,5 X27,0 XH43,5
Dimension of the packaging	25,0 X37,0 XH47,0
Colors	white
Working time without mains power	about 2 hours
Heat up time from cold	about 70 minutes
Vertical mounting	yes
Horizontal mounting	yes
Serial usb port for monitoring	yes
Nozzle tamper	yes
Serial bus for standard protocol	yes
Alarm kit	opzional

FOGGING SYSTEM

New heating system plus	yes
Coverage in a single shot (1,5 m visibility)	up to 600 m³
Coverage in a single shot (recommended density)	up to 200 m³
Max seconds of fog emission	15 sec
Max fog emitted with full fog tank	1800 m³
Number of cylinders	2
Fog tank capacity	2 x 600 ml
Shooting specification	programmable in seconds
Cylinder model	vertical / horizontal
Cylinder included	2
Double fog tank advantage	yes

STANDARD

Complies with european CE	yes
Fog fluid is certified	yes
Meets european standard	yes

ELECTRICAL SPECIFICATIONS

Power supply	230 V or 110 V
Average power consumption	37 W
Back up battery	yes
Optional demo/antirobbery kit	yes
Inputs wired arming and shooting	yes
Outputs wired	yes
Standard communication protocol	yes



UR Fog S.r.l

Operation and delivery to: Via Toscana 38 - 10099 San Mauro T.se (Torino) - Italy | Legal Office: via Giacinto Collegno 11 - 10143 Torino - Italy

Phone +39 011 0133037 E-mail: info@urfog.com