






HIKVISION®

Hybrid PRO

High speed, Stable, Reliable



AX Hybrid PRO

-  **8** onboard zones & **4** onboard outputs, expandable to **64 Zones** and **Outputs**
-  **Onboard LAN & Wi-Fi**
Optional 3/4G communication module
-  **4-ch** onboard IPC, **8** PIRCAM
-  Supports anti-sabotage for the wired siren
-  **Speed-X** BUS communication technology



Speed-X BUS Technology

Higher speed transmission

The transmission speed could reach up to **500kb/s** via Speed-X communication protocol, which is **150 times** of the traditional technology.

PIRCAM supported

Able to connect **Wired PIRCAM** for **HD image verification**, helps user or ARC verify the authenticity of alert more effectively and efficiently.

Longer transmission distance

The transmission distance of Speed-X BUS technology could reach up to **900m**, and the modules could also be connected in cascade mode to extend the distance

HIKVISION®



Wired PIRCAM

(Infrared Version)



Volumetric Coverage

Detection Range: **12m / 85.9°**



24/7 Verification

Infrared Light for dark night



Pet-Immunity

Could filter the false alarm triggered by animals(**≤ 30 KG**).



Creep-Zone Protection

Support Creep-Zone Protection.



Speed-X BUS Technology

The transmission distance of RS485 can be **900m** at the speed of **500kb/s**.




Higher Image Resolution

Support JPEG image capture with resolution of **2MP**.



GIF Verification

Up to **20 pictures** fused to a GIF.



New Peripherals

Wired LCD keypad



- Faster operational response due to **Speed-X BUS technology**
- **Tag reader & AX PRO keyfob supported**
- **Support 3EOL**
- Supports **2 on-board inputs** and **1 relay output**
- LCD screen display
- Front button cover for better protection




Wireless receiver




- Speed-X BUS technology with the speed of **500 kb/s**
- Compatible with **AX PRO wireless detectors**
- LED display to show status
- Plastic case

Zone Input Expander




- Speed-X BUS technology with the speed of **500 kb/s**
- **Long transmission distance in cascade mode**
- Support cascade connection typology
- **Support 8 onboard zones, 3EOL**
- 1 AUX power supply
- LED display to show status

The Cascade Wiring Mode




... Up to 7 expanders

Zone Output Expander



- Speed-X BUS technology with the speed of **500 kb/s**
- **Long transmission distance in cascade mode**
- Support cascade connection typology
- **4 relays onboard (High & Low Voltage)**
- LED display to show status

The Cascade Wiring Mode



... Up to 7 expanders

Management Platform



Hik-Connect



Hik-ProConnect



**Hik-Central
Professional**



3rd Party ARC Platform



Self-Monitoring via Hik-Connect

Connect easily wherever you are!



One tap to arm & disarm system



Check 7s video clips or live videos




Check system & device status



Receive instant alarm notification



Admin account can add users to manage same system



Hik-Connect



Alarm call



SMS

Hikvision Installer Platform

HIKVISION

Hik-ProConnect



**Centralizing Monitoring
& Management**




Installer Services



Firmware Upgrade



**Remote
Configuration**



Monitored by ARC

HIKVISION®



LAN/WIFI
/GPRS/3G/4G



- SIA/CID
- IP Receiver PRO



AX Hybrid PRO Family

HIKVISION



Hybrid PRO Panel



Input Expander



LCD Keypad



Output Expander



Wireless receiver



Wired Sounder



**Wired PIR/DT
Wired PIR BG**



Wired PIRCAM



**AX PRO
Wireless detector**



Magnetic Contact



**Seismic
Detector**




Panic Button



Outdoor Curtain



Outdoor Tri-tech



Hik-ProConnect




Hik-Connect

Application Scenarios

HIKVISION



Hotel



Retail



Office











Factory

Tri-X Wireless receiver Compatibility list



Wireless Peripheral	Model name
Detector	DS-PDP15P-EG2-WB (Tri-X Ellipse PIR) DS-PDD12P-EG2-WB (Tri-X Ellipse DT) DS-PDPG12P-EG2-WB (Tri-X Ellipse PIRBG) DS-PDC15-EG2-WB (Tri-X Ellipse Curtain) DS-PDMCS-EG2-WB (Tri-X Ellipse SlimMC) DS-PDWL-E-WB (Tri-X Ellipse WL) DS-PDEB1-EG2-WB (Tri-X Ellipse EB) DS-PDEBP1-EG2-WB (Tri-X Ellipse Port EB) DS-PDTPH-E-WB (Tri-X) DS-PDCL12-EG2-WB (Tri-X 360 PIR) DS-PDC10DM-EG2-WB (Tri-X DTAM Curtain) DS-PDC10AM-EG2-WB (Tri-X PIR AM Curtain)
Outdoor siren	DS-PS1-E-WB
Indoor siren	DS-PS1-I-WB
Relay	DS-PM1-O1L-WB
Relay	DS-PM1-O1H-WB

Product name	Model name	Bom	Picture	Note
Customized version control panel	DS-PHA64-LP/NP(O-STD)	302402069		
Wired LCD keypad	DS-PK1-LRT-HWB	302401919		-
3G/4G communication module	DS-PM2-S(AU)	302402012		-
Input expander	DS-PM1-I8O2-H	302402010		-
Wireless receiver	DS-PM1-RT-HWB	302402040		Compatible with AX PRO tri-x detectors

Product name	Model name	Bom	Picture	Note
Output Expander (Low current)	DS-PM1-O4L-H	302402066		<ul style="list-style-type: none"> · 4 on-board low current relays, supporting 6-36V and up to 5A current · 1 power output, maximum 500mA · 2 Speed-X bus, supporting wired output expander cascade mode
Output Expander (Power relay)	DS-PM1-O4H-H	302402065		<ul style="list-style-type: none"> · 4 on-board power relays, supporting 100-240V and up to 16A current · 2 Speed-X bus, supporting wired output expander cascade mode
Wired PIRCAM	DS-PDPC12P-EG2	314300382		<ul style="list-style-type: none"> -Detection range: 12m / 85.9° -Up to 30KG pet immunity - IR version