



PAC2 Series 3

2 Door Access Controller



Key Features

- 800 Users
- Controls 2 doors
- Split system for maximum security
- Door Open Too Long (DOTL)
- Fail Safe and Fail Secure
- 10 year data memory retention without power

12-24 Volt D.C. or 16-24 Volt A.C. operation.

800 Users.

Controls 2 doors.

Split system ensures maximum security.

Support for bulk entry of users.

Multiple configurations of the DTA inputs:

- Dedicated DTA input per door control.
- One DTA input to control both doors.
- Both DTA inputs to control Door 1 only.

Two Heavy duty 5 Amp relay contacts for lock control.

Support for Fail Safe and Fail Secure locking schemes.

Two 1 Amp N.O. relay contacts for DOTL and Door Forced alarm outputs.

Automatic door Re-lock function.

Programmable EGRESS inputs:

- Momentary release for door output.
- Hold release for door output.

Backward compatibility feature for use with the PACDL Datalogger.

10 year data memory retention, non-volatile memory.

36 month manufacturer's warranty.

Operating Voltage

11 - 30 Volts D.C.

14 - 28 Volts A.C.

Operating Current

200 mA. D.C. max

240 mA. A.C. max

Operating Temperature

0°C to 70°C

ELC Contacts

30 Volts, 5 Amp A.C./D.C.

Single Pole Single Throw

Programmable: N.O. or N.C.

DOTL Contacts:

30 Volts, 1 Amp, N.O.

Single Pole Single Throw

Dimensions

104mm x 72mm x 27mm

Weight

150g



Distributed by:

NIDAC Security

2 Cromwell Street

BURWOOD VICTORIA

AUSTRALIA 3125

Phone: +61 3 9808 6244

Email: sales@nidac.com

Web: nidac.com

Web: presco.com.au