


Sliding Gate Opener

DS-K3GL606WX-WE

Trusted Durability & Professional Security





Contents

- > Background
- **➤ Market Overview & Trends**
- > Product introduction
- >Key features
- > Product comparison
- > Typical Scenario
- > FAQ



Background

- Given the general situation of private property globally and lots of security concerns, many residential complexes and villas are equipped with sliding gates or swing gates.
- These gates are usually operated by automatic gate openers for entry and exit, providing a simple, convenient, and reliable solution.








Market Overview & Trends

Big Capacity and Great Potentia



✓ APP+

 With the widespread use of smartphones and the rise of mobile internet.



✓ Ecosystem Integration

 Integration with alarm systems, intercoms, and access control to achieve intelligent control.



✓ Power Supply

 Lithium batteries are increasingly favored, despite their higher cost.



✓ Solar Power

• Solar technology can achieve complete self-sufficiency.



DS-K3GL606WX Introduction



Packing List

- Sliding gate opener *1 Wireless Keyfob *2
- Key *2
- Installation Base *1
- Screws, Warning label





Reliability & Security

Remote control Keyfob distance 50 meters, up to 3000pcs DC Brush Motor, High Precision Gate mass – maximum 600 Kg Support anti-theft Brackets



High Performance & strong system scalability

built-in Wifi and LAN interfaces Battery-driven, max open speed 36m/Min (Battery is not included by default) Support Hik-connect app control (2025 Q2) support 50,000 persons, 250,000 cards, 3,000 Keyfobs, 500,000 events



Built-in Access Systems (Optional)






Easy configuration & maintenance

Support Seamless Installation with Competitors' Bases support Mobile web configuration with AP mode by a simple touch on NFC tags support component status self- diagnostics

DS-K3GL606WX Introduction



Relay trigger for 3rd,like 3rd remote, 3rd controller, 3rd intercom, etc..

Alarm input, for linkage function to trigger the alarm output actions.

All kinds of the 3rd IR beam supported.

DS-K3GL606WX Introduction



Other Components


- ① Gear rack (Also can be provided and welded by gate manufacturer or installer)
- 2 3/4G communication module
- ③ Anti-theft bracket
- 4 7 AH 2 x 12 V battery *2
- **⑤** Warning lamp / Siren
- **(6)** IR safety sensors (Basic component for safety)
- 7 Alarm bell, integrated with hardware
- **(8) Intercom and access control system**
- **(10)** Solar panel for charging



Integration with CCTV, Intercom, Access Control, etc



- CCTV linkage for event recording
- Intercom & Access Control linkage for visitor management & remote gate control




Surge protection




➤ Increase the Surge Impact Resistance Limit

Multiple Opening Mode


Closed




Half-open for Pedestrian




Fully-open for Vehicle



Quick Config & Delivery via mobile web





Quick Access via NFC (Android)




Mobile Web Log-in


Self-Diagnosis








Mobile Web management











User Management Gate Operation Detector Config Door config Log Query

Hikvision Gate / Door Opener Naming Rule

Model

DS-K3GL

DS-K3GW

DS-K3DG

DS-K3DR

DS-K3DL

DS-K3DW

Note


Outdoor Swing gate opener

Indoor Garage door opener

Indoor Sliding door opener

Indoor Swing door opener

Indoor Rolling shutter opener



Frequency

Letter	Explanation
6	Product position
0	Reserved for appearance
6	0-99 Weight of gate: 6 – 600Kg
W	Network Interface W: WiFi; G: 3/4G; Blank(Lan only)
WE	WE: 868Mhz keyfob WB: 433Mhz keyfob
O-STD	O-STD: Standard Hikvision Product O-NEU: Neutral Product
Push	Working mode: Push or Pull

Typical Scenario



Villa house



Residential Community



Industrial Park



Parking Lot

FAQ

- What does the letter 'G' stand for in the product model name?
 - ✓ G stands for Garage door, refer to the naming rule for more details.
- What is the maximum remote control distance of the product?
 - ✓ 50 Meter
- Which model of our product is directly competing with C Brand?
 - ✓ DS-K3GL606WX series
- Do we need to download an app for the installation and configuration of the gate opener?
 - ✓ Not necessary, user can access to gate opener directly through mobile web via NFC tag, or by Hik-Connect app.
- How many remote controls does Hikvision support at most?
 - ✓ 3000 pcs
- What is the fastest door opening speed of Hikvision's gate opener?
 - ✓ Up to 36 m/min
- Does Hikvision support anti-theft brackets?
 - ✓ Yes.